

RG11 Series

RG-11 Riser Rated, Coaxial Cable 60% Braid & Quadshield, UL Listed, 3 GHz

The Digital RG-11 Riser Rated cable is for distribution of both analog and digital television signals. It is ideally suited for Direct TV or Dishnet installations, Antenna installations, Cable TV, and other high frequency applications.

Available in both a 60% braid and a quadshield version for installation where necessary.

The cable features a 14 gauge copper clad steel center conductor, a gas expanded foamed PE dielectric, a 60% braid or 60/40% quadshield shield and a protective black riser rated PVC outer jacket.



	60%	Quadshield
Braid Coverage		
Center Conductor	0.064" 14 AWG Copper Clad Steel	
Dielectric	0.280" Gas Expanded Foam Polyethylene	
Shield 1	Bonded Aluminum-Polypropylene Tape	
Shield 2	Aluminum Braid 60% Coverage	
Shield 3	N/A	Aluminum-Polypropylene Tape
Shield 4	N/A	Aluminum Braid 40% Coverage
Jacket PVC, R Rated	0.395"	0.407"
Jacket Thickness	0.042"	0.037"
DC Resistance Center Conductor	28.5 Ω / 1000'	
Nominal Capacitance	17.05 ± 1.0 pF/Ft	
Impedance	75 ± 3 Ohms	
Velocity of Propagation	85% nominal	
Reel Size (Diameter x Width)	15 x 19"	15 x 20"
Weight	58.2 lbs	63.7 lbs

<i>Maximum Attenuation per 100 Ft</i>		
Frequency MHz	dB / 100 ft	
5	0.38	
55	0.90	
187	1.80	
211	2.00	
400	2.70	
500	3.10	
750	4.00	
860	4.70	
1000	5.00	
1200	5.90	
1450	6.60	
1750	7.70	
2150	8.80	
3000	11.00	

Ordering Information

RG-11 60% braid	1000 ft	Reel, Black	RG11-60RBR-M
RG-11 Quadshield	1000 ft	Reel, Black	RG11-QSRBR-M