

2.4 Meter Quick-Deploy Antenna System

X-Band, C-Band, Ka-Band Option

Description

Type: 2.4 Meter QD Ku-band Antenna

2.4 Meter Quick-Deploy Antenna System incorporates precision assembled reflector panels with our rugged designed for the efficient organization of high-speed communication channels in any places. To ensure quality and performance, accuracy using the latest in laser measurement techniques reflector panels are inspected for R.M.S.

Key Features

- 6-Piece Carbon fiber folding Reflector.
- Pre-Assembled Tripod Base Mount w/Pull Pins.
- Ku and Ka Band Feed Systems Available.
- Sturdy Boom Accommodates Outdoor Units.
- Adjustable Feet for Uneven Surfaces.
- Optional Lightweight Cases for Easy Transportation.

RF & Antenna Specifications		
Ku-band Linear	Receive	Transmit
Frequency, GHz	10.95-12.75	13.75-14.5
Mid-Band Gain, dBi	47.2	49.1
VSWR	1.3:1	1.3:1
3dBBeam Width, deg	0.72	0.6
Noise Temperature		
10 Deg Elevation, K	55	
20 Deg Elevation, K	50	
Typical G/T @ 10 Deg, dB/K	25.4	
Tx Power Capability, W		500
Port to Port Isolation		
Tx> Rx Rejection, dB		85
Cross-pol on Axis, dB	35	35
Insertion Loss, dB	0.4	0.25
Radiation Pattern Compliance	FCC 25.209, ITU-RS.580-6,	
First sidelobe, dB	≤ -14	
Sidelobe Envelope	29 - 25 log (1 $^{\circ}$ \leq $^{\theta}$ $<$ 20 $^{\circ}$)	
Feed Interface	WR-75 CPR	



Mechanical Specifications		
Antenna Optics	Single Offset	
Refector Aperture	2.4 Meters (7.8Feet)	
Refector Material	Carbon Fiber Reinforced Polymer	
Reflector Panels	1-piece&8-piecesegmented	
Surface Accuracy (RMS)	0.35 mm	
Elevation Travel	O to 90 $^{\circ}$ Continuous,	
Azimuth Travel	45° Fine, 360° Continuous,	
Pol. Travel	\pm 95°Continuous, Self Locking,	
Shiping Case	7 Case, airline checkable	
	(IATA-compliant)	
Case Size	Case 1: 970*640*1220mm	
	Case 2: 1120*930*630mm	
	Case 3: 1610*910*420mm	
	Case 4: 1550*450*500mm	
	Case 5: 1780*400*510mm	
	Case 6: 600*600*750mm	
	Case 7: 1150*710*680m	
Total Weight	323Kg (without BUC)	
Environmental Performance		
Operational Wind	47km/h (29mph) with ballast	
Temperature	-40° C to +50° C	
Tightness class	IP67(Dust and Water Resistant)	
Humidity	0-98%	